

Application	Model	Output Parameters
Aluminum anodizing	TBSB-2500A25V	25Vdc/2500A
	TBSB-100A30V	30Vdc/100A
	TBSB-1000A25V	25Vdc/1000A
	TBSB-750A25V	25Vdc/750A
	TBSB-700A40V	40Vdc/700A
	TBSB-500A40V	40Vdc/500A
	TBSB-300A50V	50Vdc/300A
	TBSB-200A24V	24Vdc/200A
	TBSB-100A40V	40Vdc/100A
	TBSB-100A24V	24Vdc/100A
	TBSB-50A20V	20Vdc/50A
	TBSB-16KA22V	22Vdc/16KA
	TBSB-14KA22V	22Vdc/14KA
	TBSB-12KA22V	22Vdc/12KA
	TBSB-16KA22V	22Vdc/16KA
	TBSB-12KA22V	22Vdc/12KA
	TBSB-1000A15V	15Vdc/1000A
	TBSB-18KA25V	25Vdc/18KA
	TBSB-12KA20V	20Vdc/12KA
	TBSB-20KA150V	150Vdc/20KA
	KGFB-2000A20V	20Vdc/2000A
	KGSB-50KA1000V	1000Vdc/50KA
	TBSB-22KA22V	22Vdc/22KA
	KGFB-1500A/80V	80Vdc/1500A
	TBSB-15KA/22V	22Vdc/15KA
	KGSB-4KA250V	250Vdc/4KA
	TBSB-24KA/22V	22Vdc/24KA
Colouring	DC/AC-500A/30V	DC/AC-500A/30Vdc
	DC/AC-12KA25V	DC/AC-12KA25Vdc