

Application	Model	Output Parameters
Electrolytic copper foil	TBSB-50KA/6. 5V	6. 5Vdc/50A
	TBSB-50KA/7V	7Vdc/50KA
	TBSB-45KA/6. 5V	6. 5Vdc/45KA
	TBSB-30KA/7V	7Vdc/30KA
	TBSB-45KA/8V	8Vdc/45KA
	TBSB-35KA/7. 5V	7. 5Vdc/35KA
	TBSB-50KA/8V	8Vdc/50KA
	TBSB-35KA/8V	8Vdc/35KA
	TBSB-40KA/8V	8Vdc/40KA
	TBSB-50KA/6. 3V	6. 3Vdc/50KA
	TBSB-2KA/25V	25Vdc/2KA
	TBSB-1KA/30V	30Vdc/1KA
	TBSB-200A/30V	30Vdc/200A
	TBSB-100A/30V	30Vdc/100A
	TBSB-40KA/6. 5V	6. 5Vdc/40KA
	TBSB-40000A/7V	7Vdc/40KA
	TBSB-3000A/16V	16Vdc/3000A
	TBSB-40KA/6. 5V	6. 5Vdc/40KA
	TBSB-32KA/7V	7Vdc/32KA
	TBSB-56KA/7V	7Vdc/56KA
	TBSB-4KA/18V	18Vdc/4KA
	TDSB-800A/40V	40Vdc/800A
	TBSB-700A/18V	18Vdc/700A
	TBSB-48KA/7V	7Vdc/48KA
	TBSB-5000A/7V	7Vdc/5000A
	TBFBZ-600A/8V	8Vdc/600A
	TBFBZ-30A/15V	15Vdc/30A
	TBFBZ-50A/25V	25Vdc/50A
	TBSB-50KA/10V	10Vdc/50KA
	TBSB-1000A/25V	25Vdc/1000A
	TBSB-1000A/30V	30Vdc/1000A
	TBSB-8KA/30V	30Vdc/8KA
	TBSB-36KA/6. 5V	6. 5Vdc/36KA
	TBSB-48KA/6V	6Vdc/48KA

	TBFBZ-400A/6V	6Vdc/400A
	HIFB-2500A/6V	6Vdc/2500A
	TBSB-48KA/7.5V	7.5Vdc/48KA
	TBSB-200A/7.5V	7.5Vdc/200A
	TBSB-54KA/7V	7Vdc/54KA
	TBSB-60KA/7V	7Vdc/60KA
	TBSB-60KA/8V	8Vdc/60KA
	TBSB-3000A/14V	14Vdc/3000A
	TBFB-100A/15V	15Vdc/100A
	TBSB-3600A/16V	16Vdc/3600A
	TBSB-200A/18V	18Vdc/200A
	TBSB-300A/24V	24Vdc/300A
	TDFBZ-50A/30V	30Vdc/50A
	TDSB-3000A/30V	30Vdc/3000A
	TBSB-1000A/36V	36Vdc/1000A
	TDFBG-170A/80V	80Vdc/170A