

Application	Model	Output Parameters
Furnace body heating	ACF-2000A/35V	35Vdc/2000A
	ACF-3000A/24V	24Vdc/3000A
	ACF-4000A/36V	36Vdc/4000A
	TDSB-5000A/45V	45Vdc/5000A
	TDSB-6000A/45V	45Vdc/6000A
	TDSB-10000A/45V	45Vdc/10000A
	TBSB-6000A/24V	24Vdc/6000A
	TBSB-15KA/45V	45Vdc/15KA
Smelting	TBSB-5000A/12V	12Vdc/5000A
	TBSB-6000A/12V	12Vdc/6000A
	TBSB-8000A/12V	12Vdc/8000A
	TBSB-10000A/12V	12Vdc/10000A
	TBSB-12000A/12V	12Vdc/12000A
	TBSB-15000A/12V	12Vdc/15000A
	TBSB-6000A/15V	15Vdc/6000A
	TBSB-8000A/15V	15Vdc/8000A
	TBSB-10000A/15V	15Vdc/10000A
	TBSB-12000A/15V	15Vdc/12000A
	TBSB-15000A/15V	15Vdc/15000A
	TBSB-16000A/14V	14Vdc/16000A
	TBSB-15000A/11V	11Vdc/15000A
	TBSB-18000A/11V	11Vdc/18000A
	TBSB-8000A/13V	13Vdc/8000A